



Deutsch connector DT 06-8S 4-pin/8-pin

Product characteristics

- Suitable for tilt sensors N3/N4/N5

Technical drawing

IMAGE 1/3

L1HC00.B..







IMAGE 2/3


L1HC00.B

female AMP
Micro Quadlock



L1HC00.B4

female AMP
Micro Quadlock



L1HC00.B4A

female AMP
Micro Quadlock




IMAGE 3/3

L1HC00.B

1)	RD
2)	BN
3)	BU
4)	PK
5)	GN
6)	YE
7)	WH
8)	GY

L1HC00.B4

1)	BN
2)	BU
3)	BK
4)	GY
5)	nc
6)	nc
7)	nc
8)	nc

L1HC00.B4A

1)	BN
2)	BU
3)	nc
4)	nc
5)	BK
6)	GY
7)	nc
8)	nc

Product options

IMAGE 1/1

ORDERING KEY

L1HC00		Deutsch connector DT 06-8S
	1	Cable length 1m ± 30mm
	3	Cable length 3m ± 40mm
	5	Cable length 5m ± 60mm
	0	Cable length 10m ± 80mm
	B	8-pin
	B4	4-pin
	B4A	4-pin
		Other cable materials and cable lengths on request

Article characteristics

Attribute	L1HC...B	L1HC...B4	L1HC...B4A
Cable material	PVC		
Operating temperature min.	-40 °C		
Max. operating temperature	80 °C		
Min. storage temperature	-40 °C		
Max. storage temperature	80 °C		
Connector type	Deutsch connector DT 06-8S socket		
Cable diameter	7,5 +/-0,2 mm	5,5 +/-0,3 mm	
Number of pins	8		
Number of strands	8	4	
Wire cross section	0.5 mm ²		
Cable length	Selectable (1m, 3m, 5m, 10m)		