

Tilt sensor N3

The robustly designed N3 tilt sensor has a high impact and vibration resistance so is frequently used for tilt measurement in construction machinery, industrial trucks and adverse industrial environments. The N3 tilt sensor also has a high resolution and repeating accuracy. It can be easily programmed and the neutral position adjusted with the corresponding infrared remote control.



Product characteristics

- Long service life and reliability thanks to the mechanics-free MEMS technology
- The analogue output signals can be combined with additional switching points
- Tilt range up to $\pm 60^\circ$
- IP67 protection class
- Operating range from -40°C to $+70^\circ\text{C}$
- Analogue current or voltage output, or volt free switching output via relay
- Depending on the angle, resolution up to $\leq 0.04^\circ$
- Adjustment of the neutral position possible through remote control
- Selectable switch-on and switch-off delay at the switching output

Article characteristics

Attribute	N3.A1...	N3.A2...	N3.D0....	N3.K1....	N3.K2....			
Max. switching voltage	-		48 V DC					
Max. switching current	-		1 A					
Max. switching power	-		30 W					
Polarity reversal protection	yes							
Output signal min.	-	0.5 V DC	-		0.5 V DC			
Output signal max.	-	4.5 V DC	-		4.5 V DC			
Output signal min.	4 mA		-		4 mA			
Output signal max.	20 mA		-		20 mA			
Output signal - centre position/zero position	-	2.5 V DC	-		2.5 V DC			
Output signal - centre position/zero position	12 mA		-		12 mA			
EMC immunity (Norm)	ISO 11452-5:2000 ISO7637-2:2004							
EMC emission (Norm)	DIN EN 55025:2003							
Operating voltage min.	10 V DC							
Operating voltage max.	30 V DC							
Current consumption	24 mA		36 mA					
Load resistance min.	-	10000 Ohm	-		10000 Ohm			
Load resistance max.	200 Ohm		-		200 Ohm			
Short-circuit resistance to GND	no							
Short-circuit resistance to supply	no							
Linearity error	typ. ±1 %							
Repeating accuracy	= 25°:0,2°, >25°:0,5 °							
Signal update rate	100 Hz							
Technology	MEMS							
Number of measurement axes (Number)	1							
Angle measuring range	(Selectable in 5° increments) ±5°...±60 °							
Initialisation time after power on/start-up time	500 ms							
Switching points	-		(Selectable in 0.5° increments) ±1.5°...±60 °					
Zero justification	±5°							
Vibration filter	40 Hz							
Switching output	-		2x NO					

Article characteristics

Attribute	N3.A1...	N3.A2...	N3.D0....	N3.K1....	N3.K2....					
Connection type (switching output)	-		Selectable							
Outputs	4...20mA	0,5...4,5V	Relay	4...20mA + relay	0,5...4,5V + relay					
MTTF	29.7 a	29.3 a		29.7 a	29.3 a					
Resolution	$= 25^{\circ} := 0,04^{\circ}, > 25^{\circ} := 0,14^{\circ}$									
Temperature coefficient	0.008°/K									
Protection class	IP67 DIN EN 60529									
Operating temperature min.	-40 °C									
Max. operating temperature	70 °C									
Min. storage temperature	-40 °C									
Max. storage temperature	85 °C									
Min. cable temperature range, moving	-10 °C		-5 °C	-40 °C						
Max. cable temperature range, moving	105 °C		80 °C							
Min. cable temperature range, fixed installation	-30 °C		-40 °C							
Max. cable temperature range, fixed installation	105 °C		80 °C							
Shock resistance (Norm)	DIN IEC 68 Teil 2-27									
Vibration resistance (Norm)	DIN IEC 68 Teil 2-6 DIN IEC68-2-64									
Impact resistance (Norm)	max. 50 g									
ESD insulation resistance (Norm)	ISO 10605:2008									
Torque for fastening screws	6 N m									
Weight	100 g									
Connector type	Deutsch 8 pol.									
Cable length	Variable (1m, 3m, 5m, 10m)									
Connection	Deutsch, 8-pin / cable outlet									
CE label	yes									