



Tilt sensor N4

The robustly designed N4 tilt sensor has a high impact and vibration resistance so is frequently used for tilt measurement in construction machinery, industrial trucks and adverse industrial environments. The dual-axis sensor can be easily programmed and the neutral position adjusted with the corresponding infrared remote control.

Product characteristics

- Long service life and reliability thanks to the mechanics-free MEMS technology
- The analogue output signals can be combined with additional switching points
- Tilt range up to $\pm 60^\circ$
- IP67 protection class
- Operating range from -40°C to $+70^\circ\text{C}$
- Analogue current or voltage output, or volt free switching output via relay
- Depending on the angle, resolution up to $\leq 0.04^\circ$
- Adjustment of the neutral position with remote control
- Selectable switch-on and switch-off delay at the switching output

Article characteristics

Attribute	N4.A1...	N4.A2...	N4.D0B...	N4.K1B...	N4.K2B...
Max. switching voltage	-		48 V DC		
Max. switching current	-		1 A		
Max. switching power	-		30 W		
Polarity reversal protection	yes				
Output signal min.	-	0.5 V DC	-		0.5 V DC
Output signal max.	-	4.5 V DC	-		4.5 V DC
Output signal min.	4 mA	-		4 mA	-
Output signal max.	20 mA	-		20 mA	-
Output signal - centre position/zero position	-	2.5 V DC	-		2.5 V DC
Output signal - centre position/zero position	12 mA	-		12 mA	-
EMC immunity (Norm)	ISO 11452-5:2000 ISO7637-2:2004				
EMC emission (Norm)	DIN EN 55025:2003				
Operating voltage min.	10 V DC				
Operating voltage max.	30 V DC				
Current consumption	24 mA		56 mA		
Load resistance min.	-	10000 Ohm	-		10000 Ohm
MTTF	29.6 a	29.3 a	29.6 a		29.3 a
Load resistance max.	200 Ohm	-		200 Ohm	-
Short-circuit resistance to GND	no				
Short-circuit resistance to supply	no				
Linearity error	typ. +-1 %				
Repeating accuracy	= 25°: 0,2°, >25°: 0,5 °				
Signal update rate	100 Hz				
Technology	MEMS				
Number of measurement axes (Number)	2				
Angle measuring range	(Selectable in 5° increments) ±5°...±60 °				
Initialisation time after power on/start-up time	500 ms				
Switching points	-	(Selectable in 0.5° increments) ±1.5°...±60 °			
Zero justification	±5°				
Vibration filter	40 Hz				

Article characteristics

Attribute	N4.A1...	N4.A2...	N4.D0B...	N4.K1B...	N4.K2B...
Switching output	-		2x NO		
Connection type (switching output)	-		Selectable		
Outputs	4...20mA	0,5...4,5V	Relay	4...20mA + relay	0,5...4,5V + relay
Temperature coefficient	0.008°/K				
Protection class	IP67 DIN EN 60529				
Operating temperature min.	-40 °C				
Max. operating temperature	70 °C				
Min. storage temperature	-40 °C				
Max. storage temperature	85 °C				
Min. cable temperature range, moving	-5 °C		-40 °C		
Max. cable temperature range, moving	80 °C				
Min. cable temperature range, fixed installation	-40 °C				
Max. cable temperature range, fixed installation	80 °C				
Shock resistance (Norm)	DIN IEC 68 Teil 2-27				
Vibration resistance (Norm)	DIN IEC 68 Teil 2-6 DIN IEC68-2-64				
Impact resistance (Norm)	max. 50 g				
ESD insulation resistance (Norm)	ISO 10605:2008				
Torque for fastening screws	6 N m				
Weight	100 g				
Connector type	Deutsch 8 pol.				
Cable length	Variable (1m, 3m, 5m, 10m)				
Connection	Deutsch, 8-pin / cable outlet				
CE label	yes				