

Datasheet

030PFAFMN

Mushroom push-button Ø 40, flush-mount, momentary, black



Features

| | |
|-----------------------|--|
| Range | Non-illuminated mushroom push-buttons Ø 30 |
| components | Mushroom Ø 40 |
| Code | 030PFAFMN |
| Description | Mushroom push-button Ø 40, flush-mount, momentary, black |
| Colour | Nero |
| Weight - gr | 50.0 |
| Customs Tariff | 85365080 |
| GTIN | 8052878029869 |

Datasheet

| | |
|--|--|
| Approvals | CE, UL, CSA |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Compliance with standards | UNI CEI EN 45545-2, CEI EN 61373 |
| Operating temperatures | -25° ÷ +65°C |
| Environmental operating values | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30) |
| Protection degree | IP65 (IEC-EN60529) |
| Protection against impact | IK04 (IEC-EN62262) |
| Mechanical durability | 3.000.000 Operations |
| Shock resistance | 30g duration=18ms (EN-IEC 60068-2-27) |
| Shock resistance | 50g duration=11ms (EN-IEC 60068-2-27) |
| Vibration resistance | 5g f= 2...500Hz (EN-IEC 60068-2-6) |
| Contact blocks configuration | Max no. 6 blocks (3+3) |
| Button/mushroom material (illuminated type) | PC Polycarbonate |
| Button or knob material | PA Polyamide |
| External bezel material | Anodized aluminum |
| Locking ring material | Zamak zinc alloy |
| Fixing diameter | 30.5mm - Thickness 1÷6mm |
| Tightening torque | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in) |
| Actuation type | Spring return |
| Protection against electric shock | Class I (IEC-EN61140) |
| Warranty period | 18 months |

Technical drawings

