

## Datasheet

040C2325-8E

Aluminium push-button enclosure M4 230x257x80, undrilled, with cable entry



## Features

|                       |  |
|-----------------------|--|
| <b>Range</b>          | Aluminium push-button enclosures M4 230x257 mm                             |
| <b>components</b>     | Undrilled lid  |
| <b>Code</b>           | 040C2325-8E  |
| <b>Description</b>    | Aluminium push-button enclosure M4 230x257x80, undrilled, with cable entry |
| <b>Colour</b>         | Grigio RAL7035   |
| <b>Weight - gr</b>    | 1906.0   |
| <b>Customs Tariff</b> | 85381000   |
| <b>GTIN</b>           | 8052878046675  |

## Datasheet

|  |  |
|--|--|
| <b>Approvals</b>                         | CE, UL, CSA, EAC                                   |
| <b>UL/CSA Approval</b>                   | Item will be labelled only upon specific request   |
| <b>Compliance with standards</b>         | IEC-EN62208, UL508, CSA C22.2 No.14-13             |
| <b>Operating temperatures</b>            | -40° ÷ +100°C                                      |
| <b>Protection degree</b>                 | IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250)  |
| <b>Protection against impact</b>         | IK09 (IEC-EN62262)                                 |
| <b>Manufacturing process</b>             | Shell gravity diecasting                           |
| <b>Enclosure material</b>                | Aluminum Al Si12 Cu (EN AC47000)                   |
| <b>Gasket material</b>                   | Cork rubber  |
| <b>Screw material</b>                    | Stainless steel AISI 304                           |
| <b>Tightening torque</b>                 | 2,5Nm (22.1 Lb-in)                                 |
| <b>Painting</b>                          | Polyester powder coating (except unpainted models) |
| <b>Protection against electric shock</b> | Class I (IEC-EN61140)                              |
| <b>Fitted for outdoor application</b>    | yes  |
| <b>Warranty period</b>                   | 18 months  |

## Technical drawings

---

