

## Datasheet

040X0814-8P3

Stainless steel push-button enclosure 82x142x85, 3 holes Ø 22, without cable entry



## Features

|                       |  |
|-----------------------|--|
| <b>Range</b>          | Stainless steel push-button enclosures 82x142 mm                                   |
| <b>components</b>     | 3-hole lid Ø 22  |
| <b>Code</b>           | 040X0814-8P3   |
| <b>Description</b>    | Stainless steel push-button enclosure 82x142x85, 3 holes Ø 22, without cable entry |
| <b>Weight - gr</b>    | 527.0  |
| <b>Customs Tariff</b> | 85381000   |
| <b>GTIN</b>           | 8052878048099  |

## Datasheet

|  |   |
|--|---|
| <b>Approvals</b>                         | CE  |
| <b>Compliance with standards</b>         | IEC-EN62208                                       |
| <b>Operating temperatures</b>            | -40° ÷ +100°C                                     |
| <b>Protection degree</b>                 | IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250) |
| <b>Protection against impact</b>         | IK10 (IEC-EN62262)                                |
| <b>Enclosure material</b>                | Stainless steel AISI 316L                         |
| <b>Gasket material</b>                   | Polyurethane foam                                 |
| <b>Screw material</b>                    | Stainless steel AISI 304                          |
| <b>Screw type</b>                        | M5 - cross head Phillips 2                        |
| <b>Tightening torque</b>                 | 2,5Nm (22.1 Lb-in)                                |
| <b>Protection against electric shock</b> | Class I (IEC-EN61140)                             |
| <b>Fitted for outdoor application</b>    | yes   |
| <b>Warranty period</b>                   | 18 months   |

## Technical drawings

