

# Datasheet

## 060PM2S1

Pendant push-button station with 2 1-speed push-buttons and emergency stop push-button, 1 N.C.



## Features

<b>Range</b>	Pendant push-button stations
<b>components</b>	Pendant push-button stations , 2 operators + emergency
<b>Code</b>	060PM2S1
<b>Description</b>	Pendant push-button station with 2 1-speed push-buttons and emergency stop push-button, 1 N.C.
<b>Colour</b>	Giallo
<b>Weight - gr</b>	390.0
<b>Customs Tariff</b>	8537109899
<b>GTIN</b>	8052878051440

## Datasheet

<b>Approvals</b>	CE
<b>Compliance with standards</b>	IEC-ENC60947-1, IEC-EN60947-5-1
<b>Operating temperatures</b>	-15° ÷ +80°C
<b>Protection degree</b>	IP65 (IEC-EN60529)
<b>Protection against impact</b>	IK07 (IEC-EN62262)
<b>Mechanical durability</b>	500.000 Operations
<b>Enclosure material</b>	ABS Acrylonitrile butadiene styrene
<b>Flexible cable pipe</b>	Suitable for cable D.8÷17mm
<b>Rated insulation voltage</b>	Ui 300V - Uimp 2.5KV (IEC-EN60947-1)
<b>Electrical ratings</b>	AC15: Ue 250V max AC, Ie 4A max, 1000VA
<b>Mechanical interlock</b>	yes, between opposite direction pushbuttons
<b>Warranty period</b>	18 months

## Technical drawings

