



[Article Page](#)

Product Description

inductive tube sensor





Name
Order number
Switching distance
Mounting


Switch type

Signal Type
Connection
Connection diagramm

KJ16-Q16KN-DPS-X1133
08310001928
16 mm

 non shielded

 N.O.
DC PNP
connector M12



S 19 x 11 x 78

Dimension (in mm)
Technical Specification
Special features

Tube sensor with dynamic function

Operating voltage
Max. ripple
Voltage drop
Max. load current
No load current
Leakage current
Switching hysteresis
Operating temperature
Temperature drift
Repeat accuracy
Switching state
Digital output
Time delay
Short-circuit proof
Overload protection
Reverse voltage protection
Protection category
EMC-level

Impulse delay 200ms
10 - 30 V DC
≤ 10 %
2,4 V
200 mA
≤ 10 mA
≤ 10 μA
≤ 15 %
-25 ° C to 70 ° C
≤ 10 %
≤ 10 %
LED
dynamic output function
300 ms
yes
yes
yes
IP67
DIN EN 60947-5-2: 2008



KJ16-Q16KN-DPS-X1133

Pulsotronic GmbH & Co. KG Neue Schichtstraße 14b 09366 Niederdorf Deutschland +49 (0)37296 930-200

Housing material	Plastic
Cable length	100 mm
Utilisation category	DC 13
Cable material	PUR
Cable cross	3x0.34 mm ²
Termination	Pigtail M12 3pin 100mm

Errors and omissions exceptet