


[Article Page](#)

Product Description
 Name
 Order number
 Connection

connector M12
 V2-3/W/P/10m
 44500013067

 Socket
 gewinkelt

Leaving
 Technical Specification
 Special features

Flexible cable conduit capable

Silicone-free

Digital output
 Cable
 Number of terminals
 Rated operating current at 40° C
 Rated operating voltage
 Contact resistance
 Isolation resistance
 Cable length
 Allgemeine Kennwerte
 Utilisation category
 Contact durability
 Contact material
 Contact surface material
 Contact holder
 Shell type material
 Knurled nut material
 Sealing material
 Kennwerte Leitung
 Cable material
 Cover material
 Wire isolation material
 Wire material
 Wiring diameter
 Signal wire structure
 Conductor diameter
 Outer cover diameter
 Conductor colour
 Cover colour
 Wire resistance
 Nominal operating voltage
 Test voltage unit
 Flame-retardant
 Halogen-free
 Oil-resistant
 Other resistances

offen
 3
 4 A
 250 V
 $\leq 5 \text{ m}\Omega$
 $\geq 100 \text{ M}\Omega$
 10 m
 3
 ≥ 100
 CuSn
 Ni/Au
 TPU
 TPU
 Zinkdruckguss
 NBR
 PUR
 Li9Y11Y
 PP
 Cu Litze
 3x0,34
 42x0,10mm
 1,27 mm 0,02 mm
 4,40 mm mm
 braun, blau, schwarz
 schwarzgrau RAL 7021
 max. 58Ω/km
 300 V
 3000
 nach UL-Style 20549
 nach DIN VDE 0472 Teil 815
 nach DIN EN 60811-2-1
 Highly resistant to acids, alkaline solutions and solvents, hydrolisis and microbe resistant

Errors and omissions exceptet